WHIRLPOOL

COMMERCIAL PRODUCTS

10/2014

www.whirlpool-professional.com

Whirlpool
SENSING THE DIFFERENCE

WHIRLPOOL RANGE

The range of Whirlpool Commercial products offers the perfect combination of functionality, design and quality besides offering the versatility of reduced overall dimensions where space is a premium.

Various models offer different features and capabilities in order to meet all customer requirements.

Perfect for snack bars, pubs and kiosks, small Laundries are robust and reliable.

The range consists of:

- Support Cabinet and Support Cabinet traditional line
- Ice Makers
- Micro Wave
- Support ovens
- Glass and Frontal Dishwashers
- Commercial Laundry

WHIRLPOOL

The Whirlpool professional range of cooling appliances addresses the needs of small and large operators alike.

Tables, cabinets, ice makers, shock freezers and cold rooms in the Whirlpool professional range feature the most advanced technology in the industry.

HIGH FLEXIBILITY
The variety of models, sizes, functions and technologies is capable of meeting every need and guaranteeing perfect results.

SUPERIOR QUALITY
Built to last, with a reliable structure and high-quality components.

SAVINGS
With our latest generation of cooling products, we paid close attention to energy saving, ecology, easy maintenance and, of course, operator safety.

The range consists of:
- Support refrigerators and freezers
- Glass Door refrigerators
- Ice makers

silver
white
lt gross capacity lt
number of cells
number of doors
temperature range °C
number of grid supports
number of grids included
gas
kW electrical connection rating kW
V voltage V
external dimensions mm WxDxH
kg ice production in 24 hours
Kg kg ice storage capacity

REFRIGERATORS

6th sense®

ACO 050 - ACO 051 - ACO 052 - ACO 053

- Certified for commercial use
- Optimum performance-to-price ratio
- Low noise level
- Patented smooth opening system
- Electronic control type with 6th SENSE Technology
- Digital display
- Intelligent defrost
- Ventilated
- New antibacterial filter
- Automatic water evaporation system
- High-efficiency compressor
- R600a gas type
- HCFC and CFC free
- Robust handle
- Pigeon pair with the freezer
- Reversible door
- Adjustable feet
- Grid dimensions 400x510 mm
- Perfect for kiosks, pubs, small restaurants, B&Bs

CODE	Colour	lt							kW	V	
ACO 050	○	376	1	1	+3°C +7°C	7	7	R600a	0,15	230 V~50 Hz	625x596x1790
ACO 051	●	376	1	1	+3°C +7°C	7	7	R600a	0,15	230 V~50 Hz	625x596x1790
ACO 052	○	325	1	1	+3°C +7°C	6	5 + 1 glass shelf	R600a	0,15	230 V~50 Hz	625x596x1590
ACO 053	●	325	1	1	+3°C +7°C	6	5 + 1 glass shelf	R600a	0,15	230 V~50 Hz	625x596x1590

FREEZERS

ACO 054 - ACO 055 - ACO 056 - ACO 057

- Certified for commercial use
- Optimum performance-to-price ratio
- Low noise level
- Patented smooth opening system
- Electronic control type with 6th SENSE Technology
- Digital display
- High-efficiency compressor
- R600a gas type
- HCFC and CFC free
- Robust handle
- Pigeon pair with the refrigerators
- Reversible door
- Adjustable feet
- Perfect for kiosks, pubs, small restaurants, B&Bs

CODE	Colour	lt							kW	V	
ACO 054	◯	266	1	1	-24°C -16°C	7 shelved static evaporator (5 drawers + 2 flap)	-	R600a	0,10	230 V ~ 50 Hz	625x596x1790
ACO 055	◯	266	1	1	-24°C -16°C	7 shelved static evaporator	-	R600a	0,10	230 V ~ 50 Hz	625x596x1790
ACO 056	◯	232	1	1	-24°C -16°C	6 shelved static evaporator (4 drawers + 2 flap)	-	R600a	0,08	230 V ~ 50 Hz	625x596x1590
ACO 057	◯	232	1	1	-24°C -16°C	6 shelved static evaporator	-	R600a	0,08	230 V ~ 50 Hz	625x596x1590

ADN 200/2 - ADN 201/2 - ADN 202/2 - ADN 203/2 - ADN 230/2 - ADN 221/2

- Certified for commercial use
- Optimum performance-to-price ratio
- Mechanical control
- Automatic defrost
- Ventilated
- LED internal light
- Automatic water evaporation system
- R600a gas type
- HCFC and CFC free
- Robust handle
- Reversible door
- Door lock
- Adjustable feet
- ADN 202/2, ADN 203/2, ADN 230/2 with analog thermometer
- Grid dimensions 525x360 mm (except for ADN221/2)
- Grid dimensions 488x490 mm only for ADN221/2
- Perfect for kiosks, pubs, small restaurants

CODE	Colour	lt							kW	V	
ADN 200/2		290	1	1	0°C +10°C	10	5	R600a	0,20	230 V ~ 50 Hz	600x600x1450
ADN 201/2		350	1	1	0°C +10°C	12	6	R600a	0,23	230 V ~ 50 Hz	600x600x1730
ADN 202/2		290	1	1	0°C +10°C	10	5	R600a	0,20	230 V ~ 50 Hz	600x600x1450
ADN 203/2		350	1	1	0°C +10°C	12	6	R600a	0,23	230 V ~ 50 Hz	600x600x1730
ADN 230/2		350	1	2	0°C +10°C	12	6	R600a	0,23	230 V ~ 50 Hz	600x600x1730
ADN 221/2		480	1	1	+2°C +14°C	–	5	R600a	0,25	230 V ~ 50 Hz	600x685x2025

AGB 022 - AGB 024



- AISI 304 Stainless Steel both internally and externally
- Cube ice shape
- Air condensed
- Static evaporator
- Hot gas defroster
- Roll bond system

CODE		Kg	Ice shape	Condenser type	System		kW	V	
AGB 022	24	10	cube	air	Roll bond	R134a	0,21	230 V ~ 50-60Hz	555x535x590
AGB 024	40	20	cube	air	Roll bond	R134a	0,34	230 V ~ 50-60Hz	556x535x850

PRO 25 IX

- 25 liters
- Commercial MWO **without Turntable**
- No grill
- Cavity: Stainless Steel
- Operation type: electronic
- Display type: LED
- Programs: 10
- Power Cord Length (m) : 1,5

CODE	lt	kW	kW	V	MHz	UNIT SIZE	CAVITY SIZE	kg
PRO 25 IX	25	1	input 1,5	230 V~50Hz	2450	511x421x285	328x368x206	14

WHIRLPOOL

The range of Whirlpool support ovens offers the perfect combination of functionality, design and quality besides offering the versatility of reduced overall dimensions where space is at a premium.

Various models offer different features and capabilities in order to meet all cooking requirements.

Perfect for snack bars, pubs and kiosks, these ovens and salamanders are robust and reliable.

GENERAL TECHNICAL FEATURES:

- Oven chamber with rounded corners for easy cleaning
- Intuitive digital control panel
- Storage of up to 20 cooking programs
- 3 cooking phases
- One-piece die cast bottom on all models; drainage pipe in combined convection and direct steam injection models
- Auto reversing fan
- Manual humidity control (only for combined convection and direct steam injection ovens)
- Internal lighting
- Snap-fit seals on oven chamber
- Double glazed pull-down door
- Side racks to support wire racks and trays at various heights (75mm steps), easily removable to facilitate cleaning

kW electrical connection rating kW

V voltage V

kW gas connection rating kW

external dimensions mm WxDxH

AFO 602

AFO 606

AFO 603

AFO 607

SPEEDY LINE

- Convection and combi direct steam ovens
- Perfect for catering and pastry
- Oven chamber with rounded corners for easy cleaning
- Electronic control with digital display
- 20 programmes
- 3 cooking phases
- One-piece die cast bottom
- Auto reversing fan
- Internal lighting
- Snap-fit seals on oven chamber
- Double glazed pull-down door
- 75 mm height between shelves
- Drainage pipe (for combi direct steam ovens only)
- Manual humidity control (for combi direct steam ovens only)

ELECTRIC

CODE	Heating type	**Levels**	GN	**Oven technology**	Type of control	Number of meals for which the product is suggested	kW	V	
AFO 602	Electric	**3**	2/3 and 440x345 mm	**Convection**	Electronic	25	3,2	230 V ~ 50 Hz	620x630x510
AFO 606	Electric	**3**	2/3 and 440x345 mm	**Combi direct steam**	Electronic	25	3,2	230 V ~ 50 Hz	620x680x510
AFO 603	Electric	**5**	2/3 and 440x345 mm	**Convection**	Electronic	40	3,5	230 V ~ 50 Hz	620x630x660
AFO 607	Electric	**5**	2/3 and 440x345 mm	**Combi direct steam**	Electronic	40	3,5	230 V ~ 50 Hz	620x680x660

AFO 600

AFO 604

AFO 601

AFO 605

SPEEDY LINE

- Convection and combi direct steam ovens
- Perfect for catering and pastry
- Oven chamber with rounded corners for easy cleaning
- Electronic control with digital display
- 20 programmes
- 3 cooking phases
- One-piece die cast bottom
- Auto reversing fan
- Internal lighting
- Snap-fit seals on oven chamber
- Double glazed pull-down door
- 75 mm height between shelves
- Drainage pipe (only for combi direct steam ovens)
- Manual humidity control (only for combi direct steam ovens)

ELECTRIC

CODE	Heating type	**Levels**	GN	**Oven technology**	Type of control	Number of meals for which the product is suggested	kW	V	
AFO 600	Electric	**3**	1/1 and pastry 600x400 mm	**Convection**	Electronic	40	3,5	**230 V ~ 50 Hz**	780x680x510
AFO 604	Electric	**3**	1/1 and pastry 600x400 mm	**Combi direct steam**	Electronic	40	3,5	**230 V ~ 50 Hz**	780x730x510
AFO 601	Electric	**5**	1/1 and pastry 600x400 mm	**Convection**	Electronic	70	6,3	**400 V tri ~ 50 Hz**	780x680x660
AFO 605	Electric	**5**	1/1 and pastry 600x400 mm	**Combi direct steam**	Electronic	70	6,3	**400 V tri ~ 50 Hz**	780x730x660

SUPPORT OVENS

AFO 611		Stand for ovens GN 2/3 and 440x345 mm
AFO 610		Stand for ovens GN 1/1 and pastry 600x400 mm
AFO 612		Hand shower
AFO 613		Aluminium tray 440x345 mm
AFO 614		Perforated aluminium tray 440x345 mm
AFO 618		Extraction and condensation hood for ovens GN 2/3 and 440x345 mm
AFO 616		Extraction and condensation hood for ovens GN 1/1 and pastry 600x400 mm
AFO 650		Stainless Steel Grid GN 1/1
AFO 651		Aluminium tray 600x400 mm
AFO 652*		Special Stainless steel grid for poultry cooking GN 1/1 Dim. 325x530xH151mm
AFO 653*		Special Stainless steel grid for poultry cooking GN 1/1 Dim. 325x530xH256 mm

*Only for AFO 600, AFO 604, AFO 601, AFO 605

Speedy Line Standard Equipments

CODE	Short description of the product	Standard Equipments
AFO 600	Support Ovens, Convection, Electronic, GN 1/1&600x400 mm, 3 levels, Electric	1 CHROMED GRID GN 1/1 (AFO 650/1)
AFO 601	Support Ovens, Convection, Electronic, GN 1/1&600x400 mm, 5 levels, Electric	1 CHROMED GRID GN 1/1 (AFO 650/1)
AFO 602	Support Ovens, Convection, Electronic, GN2/3& 440x345mm, 3 levels, Electric	1 CHROMED GRID 2/3 GN
AFO 603	Support Ovens, Convection, Electronic ,GN 2/3& 440x345mm, 5 levels, Electric	1 CHROMED GRID 2/3 GN
AFO 604	Support Ovens, Convection+ Steam, Electronic, GN 1/1&600x400 mm, 3 levels, Electric	1 CHROMED GRID GN 1/1 (AFO 650/1)
AFO 605	Support Ovens, Convection+ Steam, Electronic, GN 1/1&600x400 mm, 5 levels, Electric	1 CHROMED GRID GN 1/1 (AFO 650/1)
AFO 606	Support Ovens,Convection+ Steam, Electronic GN 2/3&440x345mm, 3 levels, Electric	1 CHROMED GRID 2/3 GN
AFO 607	Support Ovens, Convection+ Steam, Electronic, GN 2/3&440x345mm, 5 levels, Electric	1 CHROMED GRID 2/3 GN

Performance, reliability, safety standard, hygiene, materials, easy to use and robustness are the key features for Whirlpool Professional Dishwashers.

Whirlpool Professional range of Dishwashers has been studied to satisfy the needs of every professional user and includes:

- Glass Washers
- Frontal Dishwashers

For each product category, a range of accessories is available.

basket size mm

clear entry height mm

tank capacity lt

boiler capacity lt

tank element kW

boiler element kW

wash pump kW

power

dimensions mm WxDxH

number of cycles

standard voltage

rinse booster pump kW

water consumption lt

basket hourly output

max basket capacity (size of dish in mm)

All Whirlpool Professional Glass Washers have:

- stainless steel AISI 304 cabinet with double skinned panels
- moulded tank with stainless steel basket guides
- stainless steel wash and rinse independent rotative arms
- rinse aid pump
- self draining
- double filter system

Water supply temperature required 55° C
Water supply pressure required between 200-400 kPa
Water hardness min. 7 max. 12° F *

* Above 12° F we suggest a water softener

ADI 079

- Hot water automatic rinse
- Equipment: 2 glass baskets, 1 teaspoon rack, 1 rack for 15 saucers

CODE				lt		kW	P	kW		N		V	P	
ADI 079	**350x350**	**210**	11	2,7	1,6	2,6	0,17	2,8	420x470x585	1	120	230 V ~ 50 Hz	NO	2

- Available also with Detergent Pump **ADI 078**
- Available also with Integral Drain Pump **ADI 081**
- Available also with Detergent Pump and Integral Drain Pump **ADI 080**

ADI 071

- Hot water automatic rinse or manual cold rinse
- Equipment: 2 glass basket, 1 teaspoon rack, 1 rack for 15 saucers

CODE				lt		kW	P	kW		N		V	P	
ADI 071	**350x350**	**230**	11	2,7	1,6	2,6	0,3	2,9	420x470x635	1	120	230 V ~ 50 Hz	NO	2

- Available also with Integral Drain Pump **ADI 072**
- Available also with Detergent Pump **ADI 088**

ADI 082

- Hot water automatic rinse
- Equipment: 2 glass basket, 1 teaspoon rack, 1 rack for 15 saucers

CODE				lt		kW	P	kW		N		V	P	
ADI 082	**400x400**	**260**	14	2,7	1,6	2,6	0,17	2,8	470x515x635	1	120	230 V ~ 50 Hz	NO	2

- Available also with Drain Pump **ADI 083**

ADI 073

- Hot water automatic rinse
- Equipment: 2 glass basket, 1 teaspoon rack, 1 rack for 15 saucers

CODE				lt		kW	P	kW		N		V	P	
ADI 073	**400x400**	**300**	14	2,7	1,6	2,6	0,17	2,8	470x515x685	1	120	230 V ~ 50 Hz	NO	2

- Available also with Detergent Pump **ADI 074**
- Available also with Integral Drain Pump **ADI 075**
- Available also with Detergent Pump, Integral Drain Pump **ADI 077**

	ADN 418	kit round basket (for glass washers 350x350 mm basket) only basket ø 360x170 mm **ADI 086**
	ADN 419	kit round basket (for glass washers 400x400 mm basket) only basket ø 410x170 mm **ADI 087**
	AGS 104	cutlery rack 2 compartments 100x130x60 mm
	AGS 108	plate rack 15 small dishes 280x150x130 mm
	AGS 121	plate rack 17 small dishes 370x150x130 mm
	AGS 107	glass basket 350x350x120 mm
	AGS 116	glass basket 400x400x130 mm
	AGS 190	shallow glass basket 400x400x130 mm
	AGS 112	dishes basket 8 dishes 400x400x130 mm
	**AGS 106**	inox support 500 mm (for glass washers 350x350 mm basket)
	**AGS 110**	inox support 500 mm (for glass washers 400x400 mm basket)
	AGS 134	manual water softener 12 lt
	AGS 150	external rinse booster pump
	AGS 169	detergent pump kit

Please refer to page 22 in order to know which accessories are available for specific glass washers.

CODE	ADN 418	ADN 419	AGS 104	AGS 106	AGS 107	AGS 108	AGS 110	AGS 112	AGS 116	AGS 121	AGS 134	AGS 150	AGS 169	AGS 190
ADI 070	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 071	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 072	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 073	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
ADI 074	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
ADI 075	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
ADI 076	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
ADI 077	-	✓	✓	-	✓	✓	✓	✓	-	✓	✓	✓	✓	✓
ADI 078	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 079	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 080	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 081	✓	-	✓	✓	✓	✓	-	-	-	-	✓	✓	✓	-
ADI 082	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓
ADI 083	-	✓	✓	-	-	-	-	✓	✓	✓	✓	✓	✓	✓
ADI 088	✓	-	✓	✓	✓	✓	✓	-	-	-	✓	✓	✓	-
ADI 089	-	✓	✓	-	-	-	✓	✓	✓	✓	✓	✓	✓	✓

✓ = yes, available on demand

All Whirlpool Professional Frontal Dishwashers have:

- stainless steel AISI 304 cabinet with double skinned panels
- rinse aid pump
- hot water automatic rinse
- pressed moulded basket support

Water supply temperature required 55° C
Water supply pressure required between 200-400 kPa
Water hardness min. 7 max. 12° F *

* Aabove 12° F we suggest a water softener

AGB 650/WP

- Equipment: 1 basket for 18 dishes, 1 universal basket, 1 teaspoon rack

CODE				lt			P	kW		N		V	P	
AGB 650/WP	**500x500**	**320**	26	5,5	2,5	4,5	0,4	4,9	585x610x825	2	120/180	400 V tri ~ 50 Hz	NO	2,5

- Available also with Integral Drain Pump **AGB 651/WP**

FRONTAL DISHWASHERS

ADI 084

- Electronic panel
- Equipment: 1 basket for 18 dishes, 1 universal basket, 1 teaspoon rack

CODE				lt		kW	P	kW		N		V	P	
ADI 084	**500x500**	**320**	26	5,5	2,5	4,5	0,4	4,9	585x610x825	3	120/180+ ∞	400 V tri ~ 50 Hz	NO	2,5

AGB 648/WP

- Equipment: 1 basket for 18 dishes, 1 universal basket, 1 teaspoon rack

CODE				lt		kW	P	kW		N		V	P	
AGB 648/WP	**500x500**	**320**	26	5,5	2,5	3	0,4	3,4	585x610x825	2	120/180	230 V ~ 50 Hz	NO	2,5

- Available also with Detergent Pump **AGB 650/DP (POWER 4.9 kW)**
- Available also with Integral Drain Pump and with integrated double filter system **AGB 649/WP**
- Available also with Detergent Pump, Integral Drain Pump and with integrated double filter system **AGB 651/DP (POWER 4.9 kW)**

ADN 408

- Hot water automatic rinse
- Equipment: 1 basket for 18 dishes, 1 universal basket, 1 teaspoon rack

CODE				lt		kW	P	kW		N		V	P	
ADN 408	**500x500**	**320**	26	5,5	2,5	3,5	0,4	3,9	585x610x825	1	120	230 V ~ 50 Hz	NO	2,5

- Available also in 400 V tri ~ 50 Hz **ADN 408/1**
- Available also with Integral Drain Pump and with integrated double filter system **ADN 409**
- Available also with Integral Drain Pump in 400 V tri ~ 50 Hz and with integrated double filter system **ADN 409/1**

AGS 653/WP

- Electronic panel
- Pressed moulded tank with double filter
- Balanced door
- Equipment: 1 basket for 18 dishes, 1 universal basket, 1 teaspoon rack

CODE				lt		kW	P	kW		N		V	P	
AGS 653/WP	**500x500**	**350**	12	5,5	2	6	0,6	6,6	605x605x850	4	90/120/180+ ∞	400 V tri ~ 50 Hz	NO	2,5

- Available also with Integral Drain Pump **AGS 654/WP**
- Available also with Detergent Pump, Integral Drain Pump and Built-in Water Softener **ADN 428/1**

Accessories

	AGS 105	cutlery rack 2 compartments 100x110x150 mm
	AGS 176	basket for bulk cutlery 500x500x130 mm
	AGS 171	12 dishes basket 500x500x130 mm
	AGS 173	18 dishes basket 500x500x130 mm
	ADN 426	open basket 500x500x130 mm
	**AGS 129**	inox support 500 mm (for frontal dishwashers 605x605 mm)
	ADN 427	inox support 500 mm (for forntal dishwashers 585x610 mm)
	AGS 134	manual water softener 12 lt
	AGS 135	automatic water softener 12 lt
	AGS 150	external rinse booster pump
	AGS 169	detergent pump kit

Please refer to page 29 in order to know which accessories are available for specific frontal dishwashers.

CODE	ADN 426	ADN 427	AGS 105	AGS 129	AGS 134	AGS 135	AGS 150	AGS 169	AGS 171	AGS 173	AGS 176
ADI 084	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
ADN 408	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
ADN 408/1	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
ADN 409	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
ADN 409/1	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
ADN 425	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
ADN 428	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
ADN 428/1	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
AGB 648/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 649/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 650/DP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 650/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 651/DP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 651/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 652/DP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 652/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 653/DP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 653/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 656/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGB 657/WP	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
AGB 658/WP	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
AGB 663/WP	✓	✓	✓	-	✓	✓	✓	✓	✓	✓	✓
AGS 653/WP	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
AGS 654/WP	✓	-	✓	✓	✓	✓	✓	✓	✓	✓	✓

✓ = yes, available on demand

WHIRLPOOL COMMERCIAL PRODUCTS

The Whirlpool professional range of laundry appliances addresses the needs of small and large laundry facilities alike.

The washers, dryers and ironing equipment in the Whirlpool professional range feature the most advanced technology in the industry.

HIGH FLEXIBILITY
The variety of models, sizes, functions and technologies is capable of meeting every need and guaranteeing perfect results.

SUPERIOR QUALITY
Built to last, with a reliable structure and high-quality components.

SAVINGS
With our latest generation of washers and dryers, we paid close attention to energy saving, ecology, easy maintenance and, of course, operator safety.

The range consists of:

- Professional washers, dryers, tested and approved according to 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Kg loading capacity Kg

drum depth mm

kW electrical connection rating kW

N number of programs

G "G" factor

V voltage V

drum diameter mm

spin speed rpm

external dimensions mm WxDxH

8 kg washer and dryer set

AWM8101/PRO

- 1200 rpm
- 14 programs
- 6TH SENSE technology
- Electronic control type
- Full aquastop system
- New CIM motor (energy savings, lower noise, higher reliability, higher spinning efficiency)
- Hot and cold water fill
- Start delay
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Front Loader Washer

CODE	heating type	Kg	N			G		kW	V	
AWM 8101/PRO	electric	8	14	490	350	395	1200	2,3	230 V ~ 50 Hz	595x600x850

AWZ 8000/PRO

- Air vented dryer
- 8 programs
- 6TH SENSE technology
- Electronic control type
- Reverse tumble
- Humidity sensor
- Start delay
- Sound power level <70 db (A)
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Dryer

CODE	heating type	technology	Kg	N				kW	V	
AWZ 8000/PRO	electric	air-vented	8	8	576	452	54	2,9	230 V ~ 50 Hz	595x600x850

9 kg washer and dryer set

6th sense®

AWM9300/PRO

- 6TH SENSE technology
- 6TH SENSE speed adaption
- Electronic control type
- Full aquastop system
- Wave motion plus
- Hot and cold water fill
- Heating element hight corrosion resistant
- Silicon door bellow
- Start delay
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Front Loader Washer

CODE	heating type	Kg	N			G		kW	V	
AWM 9300/PRO	electric	9	14	490	350	395	1200	2,1	230 V ~ 50 Hz	595x600x850

3LCED9100WQ

- Electronic control type
- Robust and reliable
- Electric
- Time savings: 45 minutes per cycle
- Easy to use: 3 programs
- Extra-large door
- Door opening angle 135°
- Backsplash
- Drum finish white powder coat (more gentle on clothes)
- Speed increaser
- External exhaust type
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Dryer

CODE	heating type	technology	Kg	N				kW	V	
3LCED9100WQ	electric	air-vented	9	3	667	600	49	4,6	230 V ~ 50 Hz	686x734x997

10,5 kg Washer and Dryer set

3LWTW550YW

- 6TH SENSE technology
- Type of Agitator: Smart Agitator
- Basket Material: Stainless Steel
- Bleach Dispenser: Dump Bleach
- Fabric Softener Dispenser: Timed Flush-Drawer
- Detergent Dispenser: Drawer
- Top: Extra Wide Open Metal
- Extra Rinse Switch: On/Off
- Fabric Softener Switch: On/Off
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Top Loader Washer

NO HEATING ELEMENT
(requires hot fill with external boiler)

CODE	heating type	Kg	N				kW	V	
3LWTW5550YW	-	10,5	11	420	420	800	2	220-240 V~50 Hz	685x650x1080

3LWED5500YW

- 6TH SENSE technology
- Top: Painted
- Dryer Temperatures: 4
- Dry System: AccuDry
- Time Dry Minutes: 70
- Wrinkle Shield: On / Off 90
- Type of Control: Rotary Electronic
- Console Color: Satin Chrome
- External exhaust type
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Dryer

CODE	heating type	Kg	N				kW	V	
3LWED5500YW	electric	10,5	10	500	600	48	4,6	220-240 V~50 Hz	786x706x1090

12 kg washer

AWG1212/PRO

- Electronic control type
- Led type
- Basket Material: Stainless Steel
- Bleach Dispenser
- Fabric Softener Dispenser
- Detergent Dispenser: Drawer
- Extra Rinse Switch
- Lock
- Start Delay
- In conformity with 2006/42/EC MACHINERY DIRECTIVE (CEE Directive Machine)

Front Loader Washer

CODE	heating type	Kg	N				kW	V	
AWG1212/PRO	electric	12	9	550	379	1200	2,1	220-240 V ~ 50 Hz	813x 686x 1010

Whirlpool Europe s.r.l.
V.le Guido Borghi, 27
21025 - Comerio - (VA) ITALY
www.whirlpool-professional.com

SENSING THE DIFFERENCE

Specifications and technical information are subject to change at any time.
While every effort has been made to ensure that the information contained in this brochure is correct at time of going to press.
Whirlpool can not be held responsible for any errors or omissions that may come to light after publication.
Products offered for sale may differ from those described or illustrated here and Whirlpool reserve the right to alter specifications without prior notice.
Due to printing limitations the coulour of appliances illustrated herein cannot be guaranteed accurate, and should be used for guidance only.
If particular features, colours or measurements as important to you please check with your Whirlpool dealer before purchase.

Whirlpool is a registered trademark of Whirlpool U.S.A.